Promessa —

Ultrafabrics

Style meets stamina with Promessa. This collection features a pebbled texture and subtle sheen. With a sizable, diverse range of deep and neutral tones, it's ready for any upholstery application, especially in high-traffic spaces.



- In pursuit of our accelerated 2025 goal to include at least 50% renewable and/or recycled resources across all collections, the backcloth of Promessa will transition to include recycled polyester and responsibly sourced rayon.
- Superior durability industry-leading 16 weeks hydrolysis results
- · Blended backcloth for expanded upholstery capabilities
- 400,000 double rubs (Wyzenbeek), 180,000 rubs (Martindale)
- Bleach cleanable (1:5 bleach/water solution)
- EPA-registered antimicrobial protection does not contain triclosan and triclocarban
- SCS Indoor Advantage Gold Certification

An intelligent solution — the Ultrafabrics family of performance fabrics highlights boundary-pushing innovation where looks, feel and performance matter.



Promessa from Ultrafabrics

Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface 65% Polyester, 35% Rayon Backing

Weight:

Approx. 11.5 oz. Per Square Yard Approx. 390 Grams Per Square Metre

Thickness:

Approx. 1.1 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

Antimicrobial:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D751

ASTM E2180

Tensile Strength: BS EN ISO 1421

Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4

ISO 105 B02, Grade 6

Crocking: AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

· ASTM E84 (Adhered) - Class A

- CA TB 117-2013 Pass
- FMVSS 302 & 95/28 Annex IV Pass
- NFPA 260 Class 1
- UFAC Class 1
- CA AB 2998

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

ASTM E84 (Unadhered)

• BS EN 1021 Parts 1 & 2

• BS 5852 Source 0, 1 & 5

• IMO FTPC Part 8

(Cig, Match & Crib 5)

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



