



BURTON

GENERAL SPECIFICATIONS

Width	54"
Weight	36 oz/linear yard
Composition	Face: 100% PVC (Phthalate Free) Backing: 75% Polyester, 25% Cotton

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Strength	Fill: 64 Warp: 67
Tear Strength	Fill: 6.3 Warp: 7.1
Colorfastness to Light	300 Hours
Stain Resistant	Yes
Cold Crack	-20° F

CLEANING INSTRUCTIONS

Mild soap and water, then rinse with fresh water and wipe dry with a clean cloth. Wipe affected area with a soft cloth or soft bristle brush using a non-abrasive cleaner. Rinse with fresh water and wipe dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead/ Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

*Prop 65 Compliant
*AB2998 Compliant



*ACT® Registered Certification Marks

RECOMMENDED APPLICATIONS



WORKSPACE

HOSPITALITY

RESTAURANT

SENIOR LIVING