



CROMWELL

GENERAL SPECIFICATIONS

| | |
|---------------------------------|---|
| Width | 54" |
| Weight | 14.6 oz/linear yard |
| Composition | 89% Polyester, 9% Polyurethane, 2% Silicone |
| Backing | Polyurethane |
| Minimum Yardage Custom Color | 500 Yards |

FLAME RETARDANCY SPECIFICATIONS

| | |
|-----------------|--------|
| CAL-TB 117-2013 | Passes |
| NFPA 260 | Passes |
| UFAC Class 1 | Passes |

PERFORMANCE SPECIFICATIONS

| | |
|---------------------------------|--------------------------|
| Abrasion | 100,000+ DR |
| Colorfastness to Crocking | Wet: 5 Dry: 5 |
| Seam Slippage | Fill: 83.5 Warp: 94 |
| Tensile Strength | Fill: 79 Warp: 249 |
| Tear Strength: Tongue Tear | Fill: 10.2 Warp: 21.4 |
| Colorfastness to Light | Class 5 at 40 Hours |
| Hydrostatic Pressure (Suter) | 270+cm (maximum) |
| Brush Pill | Class 5 |

GENERAL TREATMENTS

| | |
|--------------------|--|
| Moisture Resistant | Yes |
| Bleach Resistant | Yes – 10% Dilution |
| Stain Resistant | Yes |
| Cleaning Code | SW - Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. |

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals

No added anti-microbial/anti-bacterial chemicals

PVC free

Phthalate free

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

