



KEYSTON BROS



SOFTSIDE™

AUTO COLLECTION

COMPOSITION	Apex	Aries	Buckskin w/Ab	Carbon Fiber	Caprice	*Corinthian	Geney	Gemini	*C-Grain	*Grand Prix	*Heidi	Longitude	*Madrid	*Milled Pebble	*Montana	*Monticello	*Nuance	Orion	*Oxen	Pegasus	Polaris	*Ruffino	*Sierra	Soho	Sutton	Torino	Verona	*Wallaby
Hi-Loft Flex™																												
100% Polyester Hi-Loft2™ Backing	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
Weight (oz.)	29	29	28	29	28	29	28	29	29	27	29	28	29	28	29	29	29	29	29	29	29	29	28	28	28	28	29	
Roll Size (yd.)	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	
Roll Width (in.)	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	

\*Running change from Hi-Loft2™ to Hi-Loft Flex™

FIRE CODES\*\*

	APX	ARI*	BUC*	CAR	CAP	COS	CEN	GEM	GGR	GPX	HDI*	LON	MAD	MIL*	MON	MOT	NUA	ORI*	OX*	PEG*	POL*	RUF*	SIS*	SOH	SUT*	TOR	VER*	WAL*
CA T.B. 117- 2013	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
FMVSS 302	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
IMO FTP 2010 Code MSC.307(88) Part 8, 3.1 & 3.2	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
NFPA 260- Class I	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
UFAC Fabric- Class I	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.

\*\*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

FINISHES & TREATMENTS

	APX	ARI	BUC	CAR	CAP	COS	CEN	GEM	GGR	GPX	HDI	LON	MAD	MIL	MON	MOT	NUA	ORI	OX*	PEG*	POL*	RUF*	SIS*	SOH	SUT*	TOR	VER*	WAL
PERMABLOK® ADVANCED VINYL PROTECTION	.							.																				
UV Stabilized Pigments (1,000 hours)	.		.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
Marine Quality: UV Stabilized Pigments (650 hours QUV) w/ Mildew Resistance	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
Cold Crack- CFFA 6-a Fahrenheit	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°	-10°
Abrasion CFFA-1, ASTM D-4157-02 Wyzenbeek #10 Cotton Duck	100K	50K	50K	50K	50K	50K	50K	100K	50K	50K	50K	50K	50K	50K	50K	50K	100K	50K	50K	50K	50K	50K	50K	50K	50K	50K	50K	50K



This fabric meets or exceeds these ACT performance guidelines.  
\*Certification Marks owned by ACT®

Hi-Loft flex™

The next generation of Hi-Loft™  
A new backing engineered to provide enhanced tailorability and exceptional durability.