



MURRAY

GENERAL SPECIFICATIONS

Weight	20 oz/linear yard
Composition	70% Polyester, 30% Rayon
Backing	SBR
Yarn Per Inch	40.39 EPI 34.29 PPI
Yarn Size	Fill: 3.5N Warp: 300D+3.5N
Minimum Yardage Custom Color	500 yards

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

FINISHES



PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 4.5 Dry: 4.5
Seam Slippage	Fill: 85.5 Warp: 100
Tensile Strength	Fill: 78 Warp: 153
Tear Strength	Fill: 17.3 Warp: 24.8
Colorfastness to Light	Min. Class 4 at 40 Hours
Cleaning Code	SW
Stain Resistant	Yes
Brush Pill	Class 3.5

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks