



O'MALLEY

GENERAL SPECIFICATIONS

Width	54"
Weight	19 oz/linear yard
Composition	90% Polyester, 8% Polyurethane, 2% Silicone
Backing	Polyurethane
Minimum Yardage Custom Color	500 Yards
Railroaded	No

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	90,000 DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 108 Warp: 107
Tensile Strength	Fill: 266 Warp: 274
Tear Strength: Tongue Tear	Fill: 73.6 Warp: 56.8
Colorfastness to Light	Class 4 at 40 Hours
Hydrostatic Pressure (Suter)	270+cm (maximum)
Brush Pill	Class 4.5
Bleach Resistant	Yes – 10% Dilution
Cleaning Code	SW

GENERAL TREATMENTS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned. BC. Lightly spray with 10% dilution of Household Bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

- No added flame retardant chemicals
- No added anti-microbial/anti-bacterial chemicals
- Lead / Heavy Metal Free
- BPA Free / TRIS Free / Formaldehyde Free
- Does not contain conflict materials
- CAB 2998 Compliant

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

