



SEDUCTION

GENERAL SPECIFICATIONS

Width	54"
Weight	32 oz/linear yard
Surface Composition	100% PVC
Substrate Composition	100% Polyester
Thickness	1.05 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

- No added Flame Retardant Chemicals
- No added Anti-Microbial/Anti-Bacterial Chemicals
- Phthalate Free
- Lead/Heavy Metal
- BPA Free/TRIS Free/Formaldehyde Free
- Does not contain Conflict Minerals
- CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	500,000 DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 37.8 Warp: 51
Tensile Strength	Fill: 93 Warp: 128
Tear Strength: Tongue Tear	Fill: 6.8 Warp: 7.7
Stain Resistant	Passes
Cold Crack	-20°
Colorfastness to Light	650 Hours
Bleach Resistant	Yes - 10% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

