



# ULTRALEATHER®

## GENERAL SPECIFICATIONS

Width	54"
Weight	9.7 oz/yd <sup>2</sup>
Composition	100% Polyurethane
Backing	100% Reinforced Rayon
Thickness	Approx. 0.95 mm

## PERFORMANCE SPECIFICATIONS

Abrasion	400,000 DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Strength	ASTM D 751
Stretch & Set	SAE J855
Tear Strength	ASTM D 1117
Tensile Strength	ASTM D 1117
Hydrolysis	ASTM D3690-02 SECT. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes
ASTM E84 Class 1	Passes

## RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR  
LIVING

## CLEANING INSTRUCTIONS

- Clean regularly with soap and water.
- Wipe up spills as soon as they occur.
- Remove stains with alcohol-based cleaners like Fantastik® and Formula 409®.
- Clean/disinfect using a 5:1 water/bleach solution or a commonly used healthcare disinfectant, such as CaviCide® and Virox®.
- Thoroughly rinse all solution residue with clean water.
- Air dry.



\*ACT® Registered Certification Marks