



WHISPER

GENERAL SPECIFICATIONS

Width	54"
Weight	27 oz/linear yard
Roll Size	30 yards
Composition	Vinyl / Urethane Topcoat
Backing	Hi-Loft ^{2TM}
Abrasion	100,000 DR

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

FINISHES

Napa Finish

RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR
LIVING



*ACT® Registered Certification Marks

CHARACTERISTICS

Mildew Resistant
No Heavy Metals
Formaldehyde Free
Sulfide Stain Resistant
CAB 2998 Compliant

CLEANING INSTRUCTIONS

Step 1: For light soiling, a solution of 10% household liquid dish soap in warm water, applied with a soft damp cloth. Rinse with clean water and dry.

Step 2: For heavy soiling, dampen a soft white cloth with a one-to-one (1:1) solution of Formula 409® and water or Fantastik® and water. Rub gently and rinse with a water dampened cloth.

Step 3: For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach and 90% water). Rub gently and rinse with a water dampened cloth to remove bleach concentration.

Do not use with alcohol-based cleaning agents!