

# ENVISION

## GENERAL SPECIFICATIONS

Width	54"
Weight	28 oz/linear yard
Surface Composition	100% SiO™ Silicone
Substrate Composition	100% Polyester
Gauge	0.044
Thickness	1.10 mm

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA260	Passes
UFAC Class 1	Passes
FMVSS302	Passes
IMO FTP Code 2010, Part 8	Passes
BS 5852: 2006 Crib 5	Passes
ASTM E84 (Adhered & Unadhered)	Passes

## PERFORMANCE SPECIFICATIONS

Abrasion	225,000 DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 102 Warp: 102
Tensile Strength	Fill: 279 Warp: 250
Tear Strength	Fill: 11.8 Warp: 10.7
Colorfastness to Light	500 Hours
UV Resistance	1300 Hours
Coating Adhesion	Full Bond

## GENERAL TREATMENTS

Anti-Bacterial	Passes
Anti-Microbial	Passes
Mildew Resistant	Passes
Pink Stain Resistant	Yes
Stain Resistant	Yes
Ink Resistant	Yes
Denim Dye Transfer Resistant	Yes
Bleach Resistant	Yes
Isopropyl Alcohol Resistant	Yes
Cold Crack	-20°

## RECOMMENDED APPLICATIONS



\*ACT® Registered Certification Marks

## FINISHES

