



MILTON

GENERAL SPECIFICATIONS

Width	54"
Weight	25.4 oz/linear yard
Composition	100% Polyurethane
Backing	100% Polyester
Finish	Writer's Block

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	250,000 DR
Colorfastness to Crocking	Wet: 5.0 Dry: 5.0
Seam Slippage	Fill: 80.9 Warp: 83.0
Tear Strength	Fill: 12.2 Warp: 9.3
Colorfastness to Light	200 Hours
Cleaning Code	BC - Bleach Cleanable, 10% Dilution
Anti-Microbial, Anti-Bacterial, Mildew Resistant, Denim Dye Resistant	Passes

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead/ Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

*Prop 65 Compliant

*CAB2998 Compliant

RECOMMENDED APPLICATIONS



HOSPITALITY



RESTAURANT



WORKSPACE



SENIOR LIVING



HEALTHCARE



*ACT® Registered Certification Marks



WRITER'S BLOCK™